



TEFC MOTOR			DIMENSIONS IN INCHES (FOR REFERENCE ONLY)							APPROX WEIGHT LBS
HP	RPM	NEMA	C	D	E	2F	G	H	K	
1/4	1750	56C	14,488	3,500	2,438	3,000	5,578	0,344	7,000	20
3/4	3500	56C	14,488	3,500	2,438	3,000	5,578	0,344	7,000	20
1	3500	56C	14,488	3,500	2,438	3,000	5,578	0,344	7,000	41
1-1/2	3500	56C	14,488	3,500	2,438	3,000	5,578	0,344	7,000	42
1-1/2	3500	143TC	17,050	3,500	2,750	4,000	5,578	0,344	7,000	44

WELL-SUITED FOR MULTI-PURPOSE USE THE EXTERNAL BALANCED SEAL TYPE "D" IS DESIGNED TO GIVE LONG SERVICE LIFE. TYPICAL APPLICATIONS INCLUDE DAIRY PRODUCTS, CREAM STYLE CORN, TOMATOES, BEVERAGES, ETC. ALSO APPLICABLE FOR ACID CLEANNING SOLUTIONS AND DETERGENTS.

STAINLESS STEEL CONSTRUCTION
WET PARTS - T-316 STAINLESS
CASING - T-316L STAINLESS
NON WET PARTS - T-304 STAINLESS

QC/QC+/IC+ SERIES PUMPS HAVE STANDARD STAINLESS STEEL ADAPTERS AND TYPE "D", "DG" AND "E" SEALS AVAILABLE.

QC/QC+ SERIES PUMPS ARE IN CONFORMANCE WITH 3A SANITARY STANDARDS FOR CENTRIFUGAL AND POSITIVE ROTARY PUMPS FOR MILK AND MILK PRODUCTS, NUMBER 02-10.

QC/QC+ SERIES PUMPS HAVE A STANDARD 32Ra (150 GRIT) FINISH (POLISHED), ON ALL PRODUCT CONTACT SURFACES, ALTHOUGH IF SPECIFIED, IT CAN BE ELECTROPOLISHED OR GLASS BEADED.

FOR TECHNICAL ASSISTANCE AND QUOTES
PLEASE CONTACT US:

ACCESO A #103, FRACC. IND. JURICA
76130 QUERETARO, QRO., MEXICO
PHONE: 52 (442) 218 4570 / 218 7400
FAX PHONE: 52 (442) 218 4577
www.qpumps.com
sales@qpumps.com
administration@qpumps.com