

# cast iron automatic submersible **SUMP PUMPS**



Cast iron automatic submersible sump pumps are constructed of rugged, cast iron with a screened inlet. Each has an oil-cooled, high torque 115V motor with automatic overload protection.



## FEATURES

- Automatic submersible sump pump
- Maximum pumping capacity – see performance chart below
- Heavy-duty cast iron and stainless steel construction
- 115V overload protected motor
- 10' grounded power cord
- 1-1/2" discharge pipe size
- Extremely quiet operation

### FPSC3250A

1/2 HP

**BEST 5 year warranty**

- Maximum pumping capacity to 4680 gallons per hour
- Can be used in narrow 10" diameter sump basin
- 6.3 amp motor



FPSC3250A  
FPSC2250A



### FPSC3200A

1/2 HP

**BEST 5 year warranty**

- Maximum pumping capacity to 4680 gallons per hour
- Can be used in 14" diameter sump basin
- 6.3 amp motor



FPSC3200A  
FPSC2200A



### FPSC2250A

1/3 HP

**Better 3 year warranty**

- Maximum pumping capacity to 4380 gallons per hour
- Can be used in narrow 10" diameter sump basin
- 5.8 amp motor



### FPSC2200A

1/3 HP

**Better 3 year warranty**

- Maximum pumping capacity to 4380 gallons per hour
- Can be used in 14" diameter sump basin
- 5.8 amp motor



## PERFORMANCE INFORMATION (Based on using 1-1/2" discharge pipe)

Rating	Warranty (years)	Model	HP	Switch Type	Min. Sump Diameter	Float Switch		Performance - Gallons per Hour at Discharge Head in Feet					Maximum Lift (no flow)
						On	Off	0'	5'	10'	15'	20'	
BEST	5	FPSC3250A	1/2	Vertical	10"	7-1/2"	3"	4680	4380	3840	3300	2340	28 ft.
BEST	5	FPSC3200A	1/2	Float	14"	13"	5"	4680	4380	3840	3300	2340	28 ft.
Better	3	FPSC2250A	1/3	Vertical	10"	7-1/2"	3"	4380	4020	3540	3000	1800	26 ft.
Better	3	FPSC2200A	1/3	Float	14"	13"	5"	4380	4020	3540	3000	1800	26 ft.

## ACCESSORIES (sold separately, see page 10)

### Required:

Check Valve	FP0026-10
Flood Alarm	FPW217-242
Discharge Hose Kit	FP0012-6F 1-1/4" x 24' or FP150-24 1-1/2" x 24'

### Optional: (see page 8)

Battery Back-Up	FP1800DCC or FP2800DCC
-----------------	------------------------

## TYPICAL APPLICATION

