# Industria

# **BSTF Series**



#### **Applications**


Monarch's BSTF Series of self priming centrifugal pumps are designed to be either belt driven or direct driven through a flexible coupling. This versatile design allows the option of connecting to the motor or engine of your choice.


#### **Features**

- CASING Large rugged cast iron casing provides fast priming and long life.
- **SUCTION & DISCHARGE** Sizes range from 11/4", 2" and 3" NPT.
- **IMPELLER** Semi-open, 4 vane, cast gray iron impeller with "Blind Hole" for shaft protection.
- SEAL Self lubricating mechanical seal, carbon ceramic faces. Viton and stainless steel for ag applications.
- **SHAFT** One piece, high strength stress proof steel for easy mounting to your choice of motor.
- BEARINGS Sealed double row bearings. The -83 and -125 models have two single row, deep groove, double seal ball bearings.



## **Dimensional Outline**





| Model No. | Discharge<br>A (NPT) | Suction B<br>(NPT) | Priming<br>Plug C<br>NPT | Drain<br>Plug D<br>NPT | Mounting<br>Holes E | Keyway<br>F | Shaft<br>Dia. G | Н    | J    | K    | L    | М    | N     | Р    | Q    | R    | S     | Т    |
|-----------|----------------------|--------------------|--------------------------|------------------------|---------------------|-------------|-----------------|------|------|------|------|------|-------|------|------|------|-------|------|
| BSTF-51   | 1 1/4"               | 1 1/4"             | 3/4                      | 3/4                    | .40                 | .19         | .75             | 4.00 | 2.00 | 4.25 | 7.50 | 3.20 | 10.50 | 8.10 | 6.40 | -    | 10.30 | 4.50 |
| BSTF-82   | 2"                   | 2"                 | 3/4                      | 3/4                    | .40                 | .19         | .75             | 4.25 | 2.13 | 4.00 | 8.50 | 3.20 | 11.50 | 8.90 | 6.70 | -    | 10.60 | 4.50 |
| BSTF-83   | 2"                   | 2"                 | 3/4                      | 3/4                    | .40                 | .25         | .75             | 4.25 | 2.13 | 4.00 | 8.50 | 3.20 | 11.40 | 8.40 | 6.90 | 2.00 | 12.10 | 4.50 |
| BSTF-125  | 3"                   | 3"                 | 3/4                      | 3/4                    | .40                 | .25         | .75             | 3.62 | 2.00 | 4.00 | 9.30 | 4.60 | 13.40 | 9.80 | 8.90 | 2.00 | 14.10 | 4.50 |

<sup>\*</sup>Dimensions measured in inches


## Performance Chart @ 3450 RPM

|           |    | Total Head in Feet     |     |     |     |     |     |     |    |    |  |  |
|-----------|----|------------------------|-----|-----|-----|-----|-----|-----|----|----|--|--|
| Model No. | HP | 20                     | 25  | 30  | 35  | 40  | 50  | 60  | 70 | 80 |  |  |
|           |    | Capacities in U.S. GPM |     |     |     |     |     |     |    |    |  |  |
| BSTF-51   | 1  | 68                     | 68  | 68  | 67  | 62  | 45  | 17  | -  | -  |  |  |
| BSTF-82   | 2  | 127                    | 124 | 118 | 112 | 100 | 78  | 52  | 23 | -  |  |  |
| BSTF-83   | 3  | 152                    | 152 | 150 | 147 | 142 | 125 | 100 | 43 | -  |  |  |
| BSTF-125  | 5  | 267                    | 254 | 240 | 224 | 205 | 165 | 110 | 70 | 35 |  |  |

#### **BSTF Series Frame Mount**

| Model<br>No. | Item<br>No. |        | Capacities<br>U.S. GPM | Ship<br>Wt.<br>(lbs.) | Description            |  |  |  |
|--------------|-------------|--------|------------------------|-----------------------|------------------------|--|--|--|
| BSTF-51      | 615259      | 1 1/4" | 68                     | 28                    | 3/4" shaft size, 3/16" |  |  |  |
| BSTF-82      | 615258      | 2"     | 127                    | 30                    | keyway, includes       |  |  |  |
| BSTF-83      | 615256      | 2"     | 152                    | 45                    | stainless steel and    |  |  |  |
| BSTF-125     | 615257      | 3"     | 272                    | 70                    | Viton Seal.            |  |  |  |

#### **Performance Data**





P.O. Box 12010 Oklahoma City, OK 73157-2010 Phone: 1.800.701.7894 Fax: 1.800.678.7867 www.LittleGiantPump.com