PREMIUM SHALLOW WELL JET PUMPS

APPLICATIONS

Ideal for the supply of fresh water to rural homes, farms, and cabins that have suction lifts down to 25° .

FEATURES & BENEFITS

Reoldon

- High performance shallow well jet pump
 Able to handle the water demands of large homes, cottages, and farms
- Rugged cast iron casing For years of service and reliability
- Heavy-duty dual voltage (115/230 Volt) motor with capacitor For increased starting power
- Includes factory pre-set 30/50 pressure switch Produces up to 50 psi with automatic shut-off
- Glass-filled thermoplastic impeller and diffuser For superior performance and efficient water flow



	Model	Item Number	UPC	НР	Volts	Amps	Intake	Discharge	Suction Lift	Discharge Pressure (PSI)				Max.		
										30	40	50	60	Pressure	Max. Head	
										Gallons Per Minute			PSI	- I o a a		
	RJS-50-PREM	602206	0 10121 14702 7	1/2	115/230	11.8 A @ 115 V 5.9 A @ 230 V	1-1/4" FNPT	1" FNPT	5'	12.6	10	6.1	2	65	150'	
									15'	10	7.9	4	-	60	139'	
									25'	6.9	6.2	2.5	-	55	127'	
	RJS-75-PREM	602207	0 10121 14704 1	3/4	115/230	14.4 A @ 115 V 7.2 A @ 230 V	1-1/4" FNPT	1" FNPT	5'	16.7	12.5	7	1.8	65	150'	
									15'	13.1	10	4.9	-	60	139'	
									25'	8.4	7.1	2.1	-	55	127'	
	RJS-100-PREM		8 0 10121 14705 8	1	115/230	17.6 A @ 115 V 8.8 A @ 230 V	1-1/4" FNPT	1" FNPT	5'	23.2	16.8	10.6	3.5	65	150'	
		602208							15'	19.5	14.1	7.7	-	60	139'	
									25'	13.3	11.5	5.3	-	55	127'	

Carton Specifications

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Qty. per Layer	Layers per Pallet
RJS-50-PREM	10.5"	20.5"	10.25"	38	1.28	24	6	4
RJS-75-PREM	10.5"	20.5"	10.25"	39	1.28	24	6	4
RJS-100-PREM	10.5"	20.5"	10.25"	40	1.28	24	6	4

Premium Cast Iron Shallow Well Jet Pumps

